



PRODUCT DATA SHEET:

**COMPRESSOR OIL VDL
68/150**

COMPRESSOR OIL VDL 68/150 are premium quality, mineral based compressor oils for use in reciprocating compressors and some rotary air compressors.

COMPRESSOR OIL VDL 68/150 are formulated with carefully selected base stocks fortified with additives to ensure very high resistance towards oxidation.

COMPRESSOR OIL VDL 68/150 show very low carbon deposit forming tendencies reducing the risk of fire or explosion.

COMPRESSOR OIL VDL 68/150 are recommended for the cylinder and crankcase lubrication of air or inert gas compressors operating with high discharge temperatures. COMPRESSOR OIL VDL 68/150 effectively protects against rust and oxidation.

TYPICAL PROPERTIES:			SPECIFICATIONS:
PRODUCT CODE	4382	4384	Exceeds: DIN 51506: VBL/VCL/VDL ISO 6743-3A: L-DAA/DAB/DAG/DAH
ISO VG	68	150	
DENSITY @ 15 °C	870 kg/m ³	874 kg/m ³	
VISCOSITY @ 100 °C	8.6 mm ² /s	14.5 mm ² /s	
FLASH POINT	>230°C	>230°C	
POUR POINT	- 21°C	-15°C	